# FIRE FLASH® XTREME

Art. No. 506005 men, 506006 women

# NFPA 1971-2018, NFPA 1992-2018, NFPA 1951-2013, NFPA 1977-2016, CSA Z195-2014, ASTM F2413-2018

HAIX® Secura Liner, HAIX® Sun Reflect Leather, HAIX® Climate System, HAIX® MSL System, HAIX® Lacing System, leg height: 13 inches, sole 011 Available sizes: Men 5 – 16 & half sizes, Women 5 – 12 & half sizes

Available widths: Narrow, Medium, Wide









Footwear inner liner which will never pull out or wrinkle up over time; lining is firmly secured and sealed along with the upper leather beneath the sole.

# HAIX<sup>®</sup> Sun Reflect Leather

Reduces the heating effect of the upper leather by direct sunlight. Sunlight is reflected by the leather, keeping the leather and the feet cooler.

## HAIX<sup>®</sup> Climate System

Permits air circulation with every step - moist air is released and fresh air comes in through the vent holes at the top of the boot.

#### HAIX<sup>®</sup> MSL System

Micro Soft Light: PU foam injected throughout the sole for greater shock absorption and cold/ heat insulation; extremely low weight.

## HAIX<sup>®</sup> Lacing System

Optimal fit of the boot to the foot thanks to the laces. Opening and closing is implemented with the zipper for rapid insertion. Simple two-zone lacing, so the upper lacing can be adjusted independently of the lower lacing.

UK 3 3½ 4 4½ 5 5½ 6 6½ 7 7½ 8 8½ 9

#### **Cut Protection**

Para-aramid cut protection.

#### HAIX<sup>®</sup> High Durability Cap System

Anatomically formed and well-padded steel protective toe cap to meet ASTM 2413-2018 and CSA Z195-2014 standard for personal protection - protective footwear.

#### **Protective Flexible Midsole**

Flexible protective stainless steel, cast into the sole, to meet ASTM F2413-2018 and CSA Z195-2014 standard for personal protection protective footwear.

# Upper Material

Waterproof leather, hydrophobic and breathable.

#### **Moisture Barrier**

CROSSTECH® footwear, waterproof and breathable, bacteria and chemical resistant as well as bloodborne pathogen resistant. Highly abrasion resistant and softly padded with breathable foam.

#### Sole

EU 35 36 37 37 38 39 39 40 41 41 42 43 43 44 45 45 46 47 47 48 48 49 50 50 51

4½ 5 5½ 6 6½ 7 7½ 8 8½ 9 9½ 10 10½ 11 11½ 12 12½ 13 13½ 14 14½ 15 15½ 16

Nitrile rubber shell sole, fuel-oil resistant, selfcleaning tread, high voltage resistant 14 KV.

9½ 10 10½ 11 11½ 12 12½ 13 13½ 14 14½ 15



HAIX<sup>®</sup> Lacing System







#### Insole

Anatomically formed, quick change, machine washable insert with excellent moisture absorption and quick drying qualities.

## Footbed

Anatomically formed TEXON (fleece) absorbs moisture and supports ankle.

#### Other

Newly patented easy-run lace/zip system, trefast-fix unit to allow independent lacing, pull on loop at the back, NOMEX® laces, reflective strips, profiles rubber toe cap, heel flex zone and flex zone construction around the tongue.

# Extended Wear Program

Out of warranty footwear can be refurbished with original factory parts through an extended wear package. This package includes any necessary replacement or repair of stitching, profiled rubber toe caps, insoles, and retreading of soles. Footwear will be cleaned and deodorized. HAIX footwear owners also have the option of a sole retread only or a toe cap replacement only.

### HAIX<sup>®</sup> North America Inc.

2320 Fortune Drive, Suite 120, Lexington, KY 40509 Phone 859-281-0111, Fax 859-281-0113 Toll free 866-344-HAIX (4249), www.haix.com

/ 2020
64
HAIX®
ut prior notice.
prior
/itho
t to change w
ubject to
S