Art. No. 507502 men, 507503 women

#### NFPA 1971-2018, NFPA 1992-2018, CSA Z195-2014, ASTM F2413-2018

HAIX® Secura Liner, HAIX® Sun Reflect Leather, HAIX® Ankle Flex System, HAIX® Anti Slip, HAIX® Absorption, HAIX® ID System, leg height: 14 inches, sole 017

> > athletic footwear for firefighters > lightweight

Available sizes: Men 5 - 16 & half sizes, Women 5 - 12 & half sizes

Available widths: Narrow, Medium, Wide



























HAIX® Ankle Protector



HAIX<sup>®</sup> Boot Jack



HAIX® Ankle Flex System



HAIX® High Durability Cap System



### HAIX® Secura Liner®

Footwear inner liner which will never pull out or wrinkle up over time; lining is firmly secured and sealed along with the upper leather beneath the sole.

## HAIX® Sun Reflect Leather

Reduces the heating effect of the upper leather. Sunlight is reflected by the leather, keeping the leather and the feet cooler.

### HAIX® Ankle Flex System

Ankle Flex System refers to the functionality of a pullon boot which enables it to adjust to different foot, ankle, and heel shapes providing optimal fit in the boot. Integrated flex-zones ensure high flexibility and prevents pressure points.

# **Protective Toe Cap**

Anatomically formed and well-padded composite protective toe cap to meet ASTM 2413-2018 and CSA Z195-2014 standard for personal protection protective footwear.

## **Upper Material**

Waterproof leather, hydrophobic and breathable.

CROSSTECH® footwear, waterproof and breathable. Bacteria and chemical resistant as well as bloodborne pathogen resistant. Highly abrasion resistant and softly padded with breathable fleece.

Lightweight rubber/PU sole in a sports style with sturdy road/rough terrain profile and enhanced toe-to-heel support; wear-resistant with excellent anti-slip properties - even in cold weather. The lightweight PU shock absorption wedge provides extra walking comfort and excellent thermal insulation. The flame-resistant outer sole is non-marking and offers excellent resistance against heat and fuel-oil. Its bright yellow signal marks are visible even through thick smoke.

### HAIX® Protective Flexible Midsole

Flexible protective stainless steel, cast into the PU midsole, to meet ASTM F2413-2018 and CSA Z195-2014 standard for personal protection - protective footwear.

## Footbed

Moisture-absorbent fleece insole.

Moisture wicking comfort insert with cushioning effect and antibacterial properties. Separate heel cup ensures optimized cushioning and foot guidance. "AIRFLOW" channels. "Perfect-Fit" marking for optimized boot size choice. Washable at 86°F.

# HAIX® Vario Wide Fit System

For a more individualized fit, boots fit can be adjusted with an alternate insole. Blue - narrower fit (thickest), Red - Moderate fit (average thickness), Yellow -Wider fit (thinnest). If boots feel slightly wide, HAIX® recommends using the next thickest insole; or, if slightly narrow, to use the next thinnest insole.

# HAIX® Arch Support System

Optimal ankle support and shock absorption in the arch provided by an anatomically formed last; good foot guidance and proper hold thanks to narrow heel and ankle shaft combined with added comfort through broad front foot area.

#### Other

Reflective strips, profiled toe cap, large boot straps on both sides, shin protection, boot jack

#### **Extended Wear Program**

Out of warranty footwear can be refurbished with original factory parts through an extended wear package. This package includes any necessary replacement or repair of stitching, insoles and retreading of soles. Footwear will be cleaned and deodorized. HAIX footwear owners have the option of a sole retread or toe cap replacement only.

### HAIX® North America Inc.

2320 Fortune Drive, Suite 120, Lexington, KY 40509 Phone 859-281-0111, Fax 859-281-0113 Toll free 866-344-HAIX (4249), www.haix.com

UK	3	3½	4	41/2	5	5½	6	6½	7	7½	8	8½	9	9½	10	10½	11	11½	12	12½	13	13½	14	14½	15
EU	35	36	37	37	38	39	39	40	41	41	42	43	43	44	45	45	46	47	47	48	48	49	50	50	51
US	4	41/2	5	51/2	6	61/2	7	71/2	8	81/2	9	9½	10	101/2	11	111/2	12	121/2	13	131/2	14	141/2	15	15½	16